



Ref.	Dimensions (mm)
Flange	F10 – F12
C x depth	M10x15
D x depth	M12x18
E	102
F	125
B	36
O	38.5
A	758.5
G	19.5
I	24
L	198
M	93.5
N	104.5
P	74.5
Q	93.5
R	36.5
S	30
T	168
U	239.7
V	350
Y	297.1
W	1/4" GAS
Z	518.8
Ch 1	27
Ch 2	40
Ancillaries Attachment	AA2

**Double Acting Actuators - Output Torque related to rotation angle , in Nm
(0°valve closed 90°valve open)**

ROTATION ANGLE	Air pressure supply in bar							
	2,5	3	4	5	5,6	6	7	8
0°	428.6	514.3	685.7	857.1	960	1028.6	1200	1371.4
50°	214.3	257.1	342.9	428.6	480	514.3	600	685.7
90°	321.4	385.7	514.3	642.9	720	771.4	900	1028.6

Technical Data

Max Pressure	** Min Pressure	Rotation	Stroke Adjustment	Screw Stroke Adjustment	*Moving time (sec.)		Operating temperature (°C)
					Opening	Closing	
8.4 bar	1 bar	92° -1° +91°	Not available	-	1.5	1.6	Standard -20°C +80°C High temperature -20°C +150°C Low temperature -50°C +60°C

Weight Kg	Chamber Ø (mm)	Air volume L/cycle	Theoretical n° of turns to close/open starting from neutral position	Rim pull force (N) to obtain the nominal torque	Maximum flange torque values
23.8	125	5.92	20	128.6	F10 = 500 Nm F12 = 1000 Nm

****Attention:**
for "High Temperature"
and "Low Temperature" version,
the Min Pressure is 3 bar.

*The moving time could vary on different operating and installation factors .

Operating Medium

The operating medium shall have a dew point equal to - 20 °C or, to be at least, 10 °C below the ambient temperature (ISO 8573-1, Class 3).
The maximum particle size shall not exceed 40 µm (ISO 8573-1, Class 5).